






















WATERBLAST 700 BAR 10000PSI														
 HOSE I.D.				 HOSE O.D.			 WORKING PRESSURE		 BURST PRESSURE		 MINIMUM BEND RADIUS		 WEIGHT	
DN	size	mm	inch	mm	inch	bar	psi	bar	psi	mm	inch	Kg/mt	lbs/ft	
WB700-06-04	06	-4	6,4	1/4"	16,9	0.67	700	10000	1750	25000	125	4.92	0,61	0.41
WB700-10-06	10	-6	9,5	3/8"	20,3	0.80	700	10000	1750	25000	180	7.09	0,75	0.50
WB700-12-08	12	-8	12,7	1/2"	23,2	0.91	700	10000	1750	25000	220	8.61	0,94	0.63
WB700-19-12	19	-12	19,0	3/4"	31,4	1.24	700	10000	1750	25000	280	11.02	1,63	1.10
WB700-25-16	25	-16	25,4	1"	38,1	1.50	700	10000	1750	25000	350	14.00	2,18	1.46

Applications Very high constant pressure hose for water descaling system. High abrasion resistant cover Suitable for passage of water, water-soap, emulsion. Safety factor 1:2,5.	Construction Tube: Black synthetic rubber Reinforcement: Four high tensile steel spirals Cover: black, synthetic rubber resistant to oils, abrasion and weather condition
Temperature -40°C to +90°C Operating Temperature Range -10°C to +80°C Continuous Service Temperature Range -40°F to 194°F Operating Temperature Range +14°F to 176°F Continuous Service Temperature Range	








WATERBLAST 850 BAR 12000PSI														
 HOSE I.D.				 HOSE O.D.			 WORKING PRESSURE		 BURST PRESSURE		 MINIMUM BEND RADIUS		 WEIGHT	
DN	size	mm	inch	mm	inch	bar	psi	bar	psi	mm	inch	Kg/mt	lbs/ft	
WB850-06-04	06	-4	6,4	1/4"	17,1	0.67	850	12000	2125	30000	125	4.92	0,61	0.41
WB850-10-06	10	-6	9,5	3/8"	20,5	0.81	850	12000	2125	30000	150	5.91	0,84	0.56
WB850-12-08	12	-8	12,7	1/2"	24,1	0.95	850	12000	2125	30000	260	10.50	0,97	0.65
WB850-19-12	19	-12	19,0	3/4"	31,7	1.25	850	12000	2125	30000	280	11.02	1,70	1.14
WB850-25-16	25	-16	25,4	1"	38,6	1.52	850	12000	2125	30000	355	13.98	2,26	1.52

Applications Very high constant pressure hose for water descaling system. Suitable for passage of water, water-soap, emulsion. Safety factor 1:2,5.	Construction Tube: Black synthetic rubber Reinforcement: Four high tensile steel spirals Cover: black, synthetic rubber resistant to oils, abrasion and weather condition
--	--

Temperature -40°C to +90°C Operating Temperature Range -10°C to +80°C Continuous Service Temperature Range -40°F to 194°F Operating Temperature Range +14°F to 176°F Continuous Service Temperature Range
--

WATERBLAST 1250 BAR 18000PSI															
		 HOSE I.D.				 HOSE O.D.		 WORKING PRESSURE		 BURST PRESSURE		 MINIMUM BEND RADIUS		 WEIGHT	
	DN	size	mm	inch	mm	inch	bar	psi	bar	psi	mm	inch	Kg/mt	lbs/ft	
WB1250-06-04	06	-4	6,4	1/4"	17,3	0.68	1250	18000	3125	45000	200	7.87	0,68	0.46	
WB1250-10-06	10	-6	9,5	3/8"	21,3	0.84	1250	18000	3125	45000	230	9.06	0,82	0.55	
WB1250-12-08	12	-8	12,7	1/2"	25,6	1.01	1100	16000	2750	40000	230	9.06	1,13	0.76	
WB1250-19-12	19	-12	19,0	3/4"	32,8	1.29	1000	14500	2500	36250	250	9.84	1,73	1.16	

Applications Very high constant pressure hose for water descaling system. Suitable for passage of water, water-soap, emulsion. Safety factor 1:2,5.	Construction Tube: Black synthetic rubber Reinforcement: Four high tensile steel spirals Cover: black, synthetic rubber resistant to oils, abrasion and weather condition
Temperature -40°C to +90°C Operating Temperature Range -10°C to +80°C Continuous Service Temperature Range -40°F to 194°F Operating Temperature Range +14°F to 176°F Continuous Service Temperature Range	

WATERBLAST 1380 BAR 20000PSI															
		 HOSE I.D.				 HOSE O.D.		 WORKING PRESSURE		 BURST PRESSURE		 MINIMUM BEND RADIUS		 WEIGHT	
	DN	size	mm	inch	mm	inch	bar	psi	bar	psi	mm	inch	Kg/mt	lbs/ft	
WB1380-06-04	06	-4	6,4	1/4"	17,8	0.70	1380	20000	3450	50000	125	4.92	0,73	0.49	
WB1380-10-06	10	-6	9,5	3/8"	21,5	0.85	1380	20000	3450	50000	150	5.91	1,05	0.71	
WB1380-12-08	12	-8	12,7	1/2"	28,8	1.13	1450	21000	3625	52500	250	9.84	1,87	1.26	
WB1380-19-12	19	-12	19,0	3/4"	36,2	1.43	1350	19600	3375	49000	280	11.02	2,65	1.78	
Applications Very high constant pressure hose for water descaling system. Suitable for passage of water, water-soap, emulsion. Safety factor 1:2,5.							Construction Tube: Black synthetic rubber Reinforcement: Four high tensile steel spirals up to -4, six spirals -6 and -8 Cover: black, synthetic rubber resistant to oils, abrasion and weather condition								
Temperature -40°C to +90°C Operating Temperature Range -10°C to +80°C Continuous Service Temperature Range -40°F to 194°F Operating Temperature Range +14°F to 176°F Continuous Service Temperature Range															